

## Pre-assembly control statement syntax

$$\text{SOURCE} = \left\{ \begin{array}{l} \text{read logical unit} \\ m \\ \text{poolname.filename} \end{array} \right\}$$

$$\text{OBJECT} = \left\{ \begin{array}{l} \text{punch logical unit} \\ m \\ \text{poolname.filename} [(\text{COMBINE})] \\ \text{NO} \end{array} \right\}$$

$$\text{RELOC} = \left\{ \begin{array}{l} \text{NO} \\ \text{YES} \end{array} \right\}$$

$$\text{DATE} = \text{yy/mm/dd}$$

$$\text{GO} = \left\{ \begin{array}{l} \text{NO} \\ \text{YES} \end{array} \right\}$$

$$\text{CONI} = \left\{ \begin{array}{l} \text{NO} \\ \text{YES} \end{array} \right\}$$

$$\text{MACLIB} = \left\{ \begin{array}{l} \text{SYSMAC} \\ \text{poolname}_1 [ \text{poolname}_2 [ \text{poolname}_3 \dots ] ] \end{array} \right\}$$

$$\text{WORKAREA} = \left\{ \begin{array}{l} \text{WKAnn} \\ \text{poolname}_1 [ \text{poolname}_2 [ \text{poolname}_3 \dots ] ] \end{array} \right\}$$

$$\text{LISTING} = \left\{ \begin{array}{l} \text{print logical unit} \\ m \\ \text{poolname.filename} [(\text{COMBINE})] \\ \text{NO} \end{array} \right\}$$

$$\text{XREF} = \left\{ \begin{array}{l} \text{YES} \\ \text{NO} \end{array} \right\}$$

$$\text{PARTORG} = \left\{ \begin{array}{l} 0000 \\ \text{aaaa} \end{array} \right\}$$

$$\text{COMORG} = \left\{ \begin{array}{l} 0000 \\ \text{aaaa} \end{array} \right\}$$

$$\text{COMTXT} = \left\{ \begin{array}{l} \text{YES} \\ \text{NO} \end{array} \right\}$$

$$\text{DEBUG} = \left\{ \begin{array}{l} \text{NO} \\ \text{YES} \end{array} \right\}$$

Key:

 $m$  specifies the MTIOC device number $aaaa$  specifies the address $nn$  specifies the partition number